

# EGS2108P

8-port Gigabit with 4 -port AF PoE Smart Switch

## PRODUCT OVERVIEW



EnGenius Smart PoE Switch family is special tailored for Access Points and IP surveillance applications. EGS2108P, one of the members from EnGenius Smart PoE Switch family that offers 8-Gigabit ports with IEEE802.3af PoE Support on port 1-4.

Small desktop metal housing design can fulfill the most environment request of Small Business. EGS2108P supports Power-over-Ethernet (PoE) on port 1- 4, which compliant with IEEE802.3af standards, delivering up to 15.4 watts along with the connected Ethernet cables to powered devices.

The EGS2108P supports VLAN, QoS and IGMP Snooping features for priority based application, such as IP surveillance or video/voice transitions. Moreover, it offers PoE Management on ports or even priority-base configuration.

## TECHNICAL SPECIFICATIONS

### TECHNICAL SPECIFICATIONS

|  |   |
|--|---|
| <b>Network Protocol and Standard Compatibility</b> | <ul style="list-style-type: none"> <li>• IEEE 802.3 10BASE-T (Twisted Pair Copper)</li> <li>• IEEE 802.3u 100BASE-TX (Twisted Pair Copper)</li> <li>• IEEE 802.3ab 1000BASE-T (Twisted Pair Copper)</li> <li>• IEEE 802.3z 1000BASE-X</li> <li>• IEEE802.3x full duplex flow control</li> </ul> |
| <b>Network Ports</b>                               | • 8 10/100/1000Mbps Auto Sensing Gigabit Ethernet   |
| <b>PoE Power Budget</b>                            | 61.6W   |
| <b>PoE Standard</b>                                | IEEE802.3af   |
| <b>PoE mode type</b>                               | Mode B (deliver power over pair 4-5, 7-8)   |
| <b>PoE Capable Ports</b>                           | <ul style="list-style-type: none"> <li>• Port 1 to 4: 15.4W</li> <li>• Max 15.4W on 4 10/100/1000Mbps Port</li> <li>• Max 7.5W on 4 10/100/1000Mbps Port</li> </ul>   |

### PERFORMANCE

|                             |                   |
|-----------------------------|-------------------|
| <b>Switch Capacity</b>      | 16Gbps            |
| <b>Forwarding Rate</b>      | 14.88Mpps         |
| <b>Forwarding Mode</b>      | Store and Forward |
| <b>Packet Buffer Memory</b> | 512Kbytes         |
| <b>Flash Memory</b>         | 4Mbytes           |
| <b>Jumbo Frame</b>          | 9.6K              |

### INDICATOR

|            |  |
|------------|--|
| <b>LED</b> | <ul style="list-style-type: none"> <li>• Power LED</li> <li>• Fault LED</li> <li>• PoE Max LED</li> <li>• LAN Mode LED</li> <li>• PoE Mode LED</li> <li>• Copper Ports: LAN/PoE Mode, Link/Act</li> <li>• SFT Ports: Link/Act</li> </ul> |
|------------|--|

### SOFTWARE FEATURES

#### L2 FEATURES

|                                    |  |
|------------------------------------|--|
| <b>Flow control</b>                | 802.3x flow control  |
| <b>MAC Address Table</b>           | 8K   |
| <b>Spanning Tree Protocol</b>      | 802.1Q STP   |
| <b>IGMP Snooping</b>               | Support IGMP v1/v2   |
| <b>Loopback Detection</b>          | Auto disable port when loop is detected                    |
| <b>Port Mirroring</b>              | One-to-One, Many-to-One, Supports Mirroring for Tx/Rx/Both |
| <b>Cable Diagnostics</b>           | Yes  |
| <b>Configurable Auto MDI/MDI-X</b> | Yes  |

| VLAN                             |   |
|----------------------------------|---|
| <b>802.1Q</b>                    | Yes   |
| <b>VLAN Group</b>                | • Max 64 static VLAN groups, max 4094 VIDs  |
| QoS (Quality of Service)         |   |
| <b>802.1p Quality of Service</b> | Yes   |
| <b>Queue handling</b>            | 4 priority queues supported   |
| <b>CoS based on</b>              | 802.1p Priority Queues, DSCP  |
| <b>Bandwidth Control</b>         | Port-based (Ingress/Egress, min. granularity 64 Kb/s)   |
| HARDWARE SPECIFICATIONS          |   |
| <b>Power Supply</b>              | 48V DC  |
| <b>Environment</b>               | <ul style="list-style-type: none"> <li>• Operating temperature: 0 ~ 40°C</li> <li>• Storage Temperature: -40 ~ 70°C</li> <li>• Humidity 5 ~ 95% non-condensing</li> </ul> |
| <b>Dimension</b>                 | 240mm x 105mm x 27mm  |
| <b>Weight</b>                    | 0.6 Kg  |